

SILRES[®] 604



Silicone Resins

Flaked silicone resin with good compatibility with organic resins. SILRES[®] 604 is suited as a pure binder. SILRES[®] 604 is supplied as a solvent-free solid resin.

Properties

- Is usable as a sole binder for high heat resistant powder coatings
- Improves the heat resistance of powder coatings made with organic polymers.
- Helps to improve the water resistance of powder coatings.
- Increases the weather resistance of powder coatings.
- Shows good compatibility with organic powder coating resins.

Technical data

General Characteristics

Property	Condition	Value	Method
Color	-	colorless to yellowish	-
Molecular weight (Mw)	-	approx. 2.600	-
OH content	-	3.5 - 7 %	-
Silicone content	-	100 %	-
Supply form	-	Flakes	-

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

Applications

- Heat-Resistant Coatings
- Industrial Coatings
- Powder Coatings

Application details

SILRES® 604 can be used for the following applications:

- base material for powder coatings
- heat resistant up to 650 °C
- white formulation up to 270 °C without obvious yellowing

Packaging and storage

Packaging

300 kg carton (12 x 25 kg paper sack)

Storage

Further information for storage: Store in a dry and cool place.

The 'Best use before end' date of each batch is shown on the product label.

Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case however, the properties required for the intended use must be checked for quality assurance reasons.

Safety notes

Comprehensive instructions are given in the corresponding Material Safety Data Sheets. They are available on request from WACKER subsidiaries or may be printed via WACKER web site <http://www.wacker.com>.

QR Code SILRES® 604



For technical, quality or product safety questions, please contact:

Wacker Chemie AG, Gisela-Stein-Strasse 1, 81671 Munich, Germany
productinformation@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.